



Salad & Sandwich Prep Tables

STANDARD FEATURES

- DURABLE STAINLESS STEEL**
 Our prep tables boast a sturdy stainless steel exterior and interior finish and galvanized back panel providing strength and durability.
- ERGONOMICALLY DESIGNED SOLID DOORS**
 Standard doors come with easy grip handles and self closing/120° stay open door feature, working together for customer convenience.
- MAGNETIC DOOR GASKET**
 Built of one piece, the gasket is removable without tools for ease of cleaning and replacement. Door's in step design gives added protection to the gasket.
- EFFICIENT REFRIGERATION SYSTEM**
 Factory engineered oversized and balanced refrigeration system. CFC-free R-134A Refrigerators maintain temperature from 33°F to 41°F. Forced air design underneath pans to keep products fresh.
- FRONT BREATHING**
 Allows unrestricted placement of the unit.
- HIGH DENSITY POLYURETHANE INSULATION**
 2" Ecomate® CFC-free polyurethane insulation foamed in place for extra strength and energy efficiency, while being environmentally friendly with zero ozone depletion potential (ODP) and zero global warming potential (GWP).
- INSULATED LIDS**
 Removable insulated lids keep food fresh and cold by reducing condensation.
- REVERSIBLE & EASY CLEANING CUTTING BOARD**
 The full length removable white polyethylene cutting board provides a comfortable 10" operation space.
- STANDARD WITH FULL SETS OF 1/6th PANS, 4" DEEP**
 It also accommodate 6" deep pans (except for APTS-27; has two 1/9th size pans).

- APTS-27-8
- APTS-48-12
- APTS-60-16
- APTS-72-18



APTS-27-8



APTS-60-16



APTS-72-18

OPTIONS & ACCESSORIES


Additional epoxy coated shelves / 2.5" Casters /
 6" Adjustable stainless steel legs / 220V-50 cycles- 1 phase




MODEL	DOORS	TOP PANS	SHLVS.	AMPS	HP	VOLTAGE	NEMA PLUG	CORD LENGHT	CABINET DIMENSIONS			SHIPPING	
									L	D*	H**	Wt.	Cubes
REFRIGERATOR													
APTS-27-8	1	8	1	2.7	1/6	115/60/1	5-15P	8'	27"	30"	38"	188	33
APTS-48-12	2	12	2	5.4	1/4	115/60/1	5-15P	8'	48"	30"	38"	280	55
APTS-60-16	2	16	2	6.7	1/3	115/60/1	5-15P	8'	60"	30"	38"	320	68
APTS-72-18	3	18	3	6.7	1/3	115/60/1	5-15P	8'	72"	30"	38"	370	81

* Depth does not include 1" rear bumper **Height does not include 5" overall for casters


APTS-27-8 Top




APTS-27-8 Front




APTS-48-12 Top




APTS-48-12 Front




APTS-60-16 Top




APTS-60-16 Front




APTS-72-18 Top



APTS-72-18 Front




APTS-Common View




Open Lid

APTS-Common View



Closed Lid

* Specifications



CABINET CONSTRUCTION

- EXTERIOR: Stainless steel, galvanized steel back.
- INTERIOR: Stainless steel.
- CABINET & DOOR : Entire foamed-in-place high-density, Ecomate® CFC-free, polyurethane insulation. Coved corner floor to meet NSF requirements.
- Casters: 4" Diameter swivel casters, front two with brakes.
- SHELVES: 1 Adjustable epoxy coated wire shelves per door.

DOORS

- Stainless steel exterior with ABS interior liner.
- One piece constructions magnetic gasket, removable without tools for easy cleaning.
- Self-closing doors with 120° stay open feature and recessed handles for convenient loading and unloading.

REFRIGERATION SYSTEM

- Oversized and balanced refrigeration system.
- R-134 A holding temperature at 33°F to 41°F Refrigerators
- Self-contained capillary tube system using environmentally-friendly and CFC-free refrigerant.
- Front breathing allows unrestricted placement of the unit.
- Large fan motor and fan blades for better air circulation
- Self contained system, no plumbing necessary

ELECTRICAL

- The whole unit is completely pre-wired at factory with cord and plug set included and ready for final connection to a 115/60/1 phase.
- 220V / 50Hz / 1Ph available from factory.

WARRANTY

Continental US & Canada :

- **One year** labor and parts warranty.
- **Five year** compressor warranty.
- **International:** one year parts only.

* Asber's specification are subject to change without notice as we continue to make product improvements.